


HSL-TB32-MD

32-CH Separate I/O Terminal Base



Specifications


■ General Description	Separate I/O wiring connection for HSL I/O modules Every I/O points uses 3-pin connector Pin definition is signal/ground/power (from left to right) Separate fuse protection for each I/O points (jumper selection) Supports common/separate DC power supply (jumper selection) Terminator resistor on board (jumper selection) Interlocking design for rugged installation Power LED indicator DIN rail mounting Power and ground included for each signal channel	■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
		■ Power Supply	22 V to 26 Vdc
		■ Dimensions	129 x 107 x 47.5 mm (W x L x H)

Support Modules

- HSL-DI16DO16-M-NN/-PN/-PP/-NP
- HSL-DI32-M-N/P
- HSL-DO32-M-N/P

HSL-TB32-M-DIN

32-CH I/O Terminal Base



Specifications


■ General Description	Field I/O wiring connection for HSL I/O modules Spring terminal for easy field wiring Power and ground included for each signal channel Interlocking design for rugged installation Power LED indicator DIN rail mounting Terminator resistor on board	■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
		■ Power supply	22 V to 26 Vdc
		■ Dimensions	128.5 x 85.5 x 108 mm (W x L x H)

Support Modules

- HSL-DI16DO16-M-NN/-PN/-PP/-NP
- HSL-DI32-M-N/P
- HSL-DO32-M-N/P
- HSL-R8DI16-M-N/-P
- HSL-AI16AO2-M-VV/-AV

HSL-TB32-U-DIN

32 Points Universal Terminal Base



Specifications


■ General Description	Field I/O wiring connection for HSL I/O modules Spring terminal for easy field wiring Power and ground included for each signal channel Interlocking design for rugged installation Power LED indicator DIN rail mounting Terminator resistor on board	■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
		■ Power Supply	22 V to 26 Vdc
		■ Dimensions	126 x 120.1 x 107.3 mm (W x L x H)

Support Modules

- HSL-DI16DO16-DB-NN/-PN/-PP/-NP
- HSL-DI32-DB-N/P
- HSL-DO32-DB-N/P

HSL-TB64

64 Points High Density Terminal Base



Specifications

■ General Description	Field I/O wiring connection for HSL I/O modules Spring terminal for easy field wiring Power and ground included for each signal channel Interlocking design for rugged installation Power LED indicator DIN rail mounting Terminator resistor on board	■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
		■ Power Supply	22 V to 26 Vdc
		■ Dimensions	168.7 x 120.1 x 107.1 mm (W x L x H)

Support Modules

- HSL-DI16DO16-DB-NN/-PN/-PP/-NP
- HSL-DI32-DB-N/P
- HSL-DO32-DB-N/P

1

Software & Utilities

2

DAQ

3

PXI

4

Modular Instruments

5

GPB & Bus Expansion

6

PAC

7

Motion

8

Real-time Distributed I/O

9

Remote I/O

10

Communications

11

Vision

12

Fanless I/O Platforms

13

cPCI & Industrial Computers

14

Accessories