



Features

- Supports 6-slot ISA and PICMG backplane applicable
- One 5.25" and one 3.5" external drive bay and one 3.5" internal drive bay
- Drive bay with shock and vibration resistant design
- Replaceable and easy-to-clean air filter
- 12cm cooling fan for better ventilation (85CFM)
- Two USB and one PS/2 keyboard connector on front panel

Specifications

Dimensions	10 in x 6.9 in x 16.5 in (254 mm x 175 mm x 419.1 mm) (W x H x D)
Drive Bays	One 5.25" and one 3.5" front accessible drive bays One internal 3.5" drive bay
Construction	Heavy-Duty Steel
Color	Standard: beige
Cooling Fans	In: one 120 mm x 120 mm x 25 mm ball bearing fan (85CFM)
Front Panel	Two LEDs: HDD active and system power System reset switch and ATX power switch Two USB and one PS/2 keyboard connector
Rear Panel	Supports 6-slot passive backplane Supports PS2 form factor ATX power supply
Carton Size	21 in x 17.3 in x 12.4 in (533 mm x 440 mm x 315 mm)
Weight	Net 6.4 kg (14.1 lb)

Backplane Options

Model Name	PICMG® CPU	PCIe x1	PCIe x4	PCIe x16	PCI	ISA	PSU Connector
EBP-5E1	1	--	--	1	--	--	ATX
HPCI-6S4	1	--	--	--	4	1	ATX/AT

Mechanical Layout



Power Supply Options

Model Number	Watt	Input Range	Output (Max.)						Current Type
			+5V	+3.3V	+12V	-12V	-5V	+5Vsb	
APS-935XA-EPS12	350 W	90 – 264 VAC Full Range	35 A	28 A	26 A	0.8 A	0.5 A	2 A	EPS12V
APS-940XA-ATX12	400 W	90 – 264 VAC Full Range	35 A	28 A	30 A	0.8 A	0.5 A	2 A	ATX12V

Ordering Information

Model Number	Color	Backplane	Power Supply
NS-607B-6S4-350	Beige	HPCI-6S4	APS-935XA-EPS12

Dimensions

Units: mm

