

RK-608B, RK-608MB

Wallmount Chassis for 10-slot Backplane & Motherboard



Features

- Supports 8~10 slot PICMG backplane (RK-608B) and motherboard (RK-608MB)
- Two 5.25" and two 3.5" external drive bays and one internal 3.5" drive bay
- Drive bay with shock and vibration resistant design
- Replaceable and easy-to-clean air filter
- 12cm cooling fan for better ventilation (85CFM)
- Two USB and one PS/2 keyboard connector on front panel

Specifications

Dimensions	13 in x 7.7 in x 16 in (330 mm x 196 mm x 406 mm) (W x H x D)
Drive Bays	One 5.25" and two 3.5" front accessible drive bays or four internal 3.5" drive bays
Construction	Heavy-Duty Steel
Color	Standard: beige
Cooling Fans	In: one 120 mm x 120 mm x 25 mm ball bearing fan(85CFM)
Front Panel	Two LEDs: HDD active and system power System reset switch and ATX power switch Two USB and one PS/2 keyboard connector
Rear Panel	Supports 10-slot passive backplane (RK-608B) Supports microATX & ATX motherboard (RK-608MB) Supports PS2 form factor ATX power supply
Carton Size	20.9 in x 13.2 in x 18.1 in (530 mm x 335 mm x 460 mm)
Weight	Net 7.8 kg (17.2 lb)

Backplane Options

Model Name	PICMG [®] CPU	PCIe x1	PCIe x4	PCIe x16	PCI	ISA	PSU Connector
HPCI-9S7U	2	--	--	--	7	1	ATX/AT

Mechanical Layout



Power Supply Options

Model Number	Watt	Input Range	Output (Max.)						Current Type
			+5V	+3.3V	+12V	-12V	-5V	+5Vsb	
APS-935XA-EPS12	350 W	90 – 264 VAC Full Range	35 A	28 A	26 A	0.8 A	0.5 A	2 A	EPS12V
APS-940XA-ATX12	400 W	90 – 264 VAC Full Range	35 A	28 A	30 A	0.8 A	0.5 A	2 A	ATX12V

Ordering Information

Model Number	Color	Backplane	Power Supply
NS-608B-9S7U-350	Beige	HPCI-9S7U	APS-935XA-EPS12
NS-608MB-350	Beige	--	APS-935XA-EPS12

Dimensions

Units: mm

